



MAXAM

MS963

IMPLEMENT I1

Ribbed implement I1 pattern for high flotation and minimal soil disturbance.

- Extra wide tread design provides maximum flotation
- Deep undertread and reinforced shoulder for improved stubble resistance
- Special cut resistant compound
- Low rolling resistance

Applications



Size	PR	Type	Rim	O.D.		S.W		T.D.		Infl. P.		LI/SS
				in	mm	in	mm	32nds	mm	psi	kPa	
6.70-15	6	TL	4.00	28.4	721.0	7.0	178.0	7	6	44	300	97B
7.60-15	8	TL	5.50	28.9	734.0	7.6	193.0	8	6	52	360	106B
9.5L-14	8	TL	7.00	29.4	747.0	9.5	241.0	9	7	44	300	111B
9.5L-15	8	TL	7.00	30.0	762.0	9.6	244.0	10	8	44	300	112B
9.5L-15	12	TL	7.00	30.0	762.0	9.6	244.0	10	8	64	440	121B
11L-14	8	TL	8.00	29.7	754.0	11.0	279.0	9	7	36	250	112B
11L-15	8	TL	8.00	30.2	767.0	10.8	274.0	10	8	36	250	113B
11L-15	12	TL	8.00	30.2	767.0	10.8	274.0	10	8	52	360	121B
11L-16	8	TL	8.00	31.6	803.0	11.0	279.0	11	9	36	250	115B
12.5L-15	10	TL	10.00	32.0	813.0	12.1	307.0	11	9	44	300	123B
12.5L-15	12	TL	10.00	32.0	813.0	12.1	307.0	11	9	52	360	127B
12.5L-16	14	TL	10.00	33.4	848.0	12.5	318.0	11	9	56	385	130B
16.5L-16.1	10	TL	14.00	40.8	1036.0	16.5	419.0	15	12	36	250	138B
16.5L-16.1	14	TL	14.00	40.8	1036.0	16.5	419.0	15	12	48	330	145B
21.5L-16.1	10	TL	18.00	44.5	1130.0	21.5	546.0	14	11	28	190	146B
21.5L-16.1	14	TL	18.00	44.5	1130.0	21.5	546.0	14	11	36	250	152B